

# DH-HAC-HFW2401D

4MP HDCVI WDR IR Bullet Camera

## HDCVI



- 120dB True WDR, 3DNR
- Max 4MP real-time
- HD and SD dual-output
- 3.6mm fixed lens
- Max. IR length 80m, Smart IR
- IP67, DC12V



### System Overview

Experience superior clarity of real-time 4Mega-pixel video with the simplicity of using existing coaxial infrastructure. The 4MP HDCVI camera presents high quality image with clear details and accurate color rendition, and supports 120dB true WDR for applications under complex dynamic range. It offers various motorized/fixed lens models with multi-language OSD and HD&SD dual-output. The higher resolution and complete features make the 4MP HDCVI camera an ideal choice for mid to large-size business and common projects where both highly reliable surveillance and construction flexibility are concerned.

### Functions

#### 4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio\*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the HCVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

\* Audio input is available for some models of HDCVI cameras.

#### Long Distance Transmission

HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 700m transmission for 4MP HD video via coaxial cable, and up to 300m via UTP cable.\*

\*Actual results verified by real-scene testing in Dahua's test laboratory.

#### Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

#### Multi-outputs

The camera supports HDCVI and CVBS signal outputs simultaneously with two BNC connectors. Multi-outputs facilitates construction in such situations as debugging through a tester. It also offers the possibility for cooperating with multiple devices including analog matrix or monitor.

### Smart IR

The camera is designed with array LED IR illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object come closer to the camera.

### Wide Dynamic Range

Embedded with industry leading wide dynamic range (WDR) technology, vivid pictures are achieved even in the most intense contrast lighting conditions. True WDR (120dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

### Advanced 3DNR

3DNR is noise reduction technology that detects and eliminates random noises by comparing two sequential frames. Dahua's advanced 3DNR technology allows remarkable noise reduction with little impact to sharpness, especially under limited lighting condition. Besides, the advanced 3DNR effectively decreases the band width and saves the storage space.

### Large Aperture Lens

The camera adopts high-end F1.5 large aperture lens. With higher amount of absorbed light, the camera presents an impressive lowlight performance.

### Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments. Supporting  $\pm 25\%$  input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.

### Technical Specification

#### Camera

|                          |                          |
|--------------------------|--------------------------|
| Image Sensor             | 1/3" CMOS                |
| Effective Pixels         | 2688(H)×1520(V), 4.1MP   |
| Scanning System          | Progressive              |
| Electronic Shutter Speed | 1/3s~1/300,000s          |
| Minimum Illumination     | 0.03Lux/F1.5, 0Lux IR on |
| S/N Ratio                | More than 65dB           |
| IR Distance              | Up to 80m (262feet)      |
| IR On/Off Control        | Auto / Manual            |
| IR LEDs                  | 2                        |

#### Lens

|                      |                         |
|----------------------|-------------------------|
| Lens Type            | Fixed lens / Fixed iris |
| Mount Type           | Board-in                |
| Focal Length         | 3.6mm                   |
| Max Aperture         | F1.5                    |
| Angle of View        | H: 78°                  |
| Focus Control        | N/A                     |
| Close Focus Distance | 1500mm<br>59.06"        |

#### Pan / Tilt / Rotation

|                   |   |
|-------------------|---|
| Pan/Tilt/Rotation | Pan: 0° ~ 360°<br>Tilt: 0° ~ 87°<br>Rotation: 0° ~ 360° |
|-------------------|---|

#### Video

|                 |   |
|-----------------|---|
| Resolution      | 4MP (2560×1440)   |
| Frame Rate      | 25fps@4MP, 25/30fps@1080P, 25/30fps@720P  |
| Video Output    | 1-channel BNC HDCVI high definition video output<br>& 1-channel BNC CVBS video output |
| Day/Night       | Auto (ICR) / Manual   |
| OSD Menu        | Multi-language  |
| BLC Mode        | BLC / HLC / WDR   |
| WDR             | 120dB   |
| Gain Control    | AGC   |
| Noise Reduction | 2D/3D   |
| White Balance   | Auto / Manual   |
| Smart IR        | Auto / Manual   |

#### Certifications

|                |   |
|----------------|---|
| Certifications | CE (EN55032, EN55024, EN50130-4)<br>FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014)<br>UL (UL60950-1+CAN/CSA C22.2 No.60950-1) |
|----------------|---|

#### Electrical

|                   |                        |
|-------------------|------------------------|
| Power Supply      | 12V DC ±25%            |
| Power Consumption | Max 7W (12V DC, IR on) |

#### Environmental

|  |   |
|--|---|
| Operating Conditions                   | -30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH<br>* Start up should be done at above -30°C (-22°F) |
| Storage Conditions                     | -30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH   |
| Ingress Protection & Vandal Resistance | IP67  |

#### Construction

|              |   |
|--------------|---|
| Casing       | Aluminium                                 |
| Dimensions   | 241.8mm×90.4mm×90.3mm (9.52"×3.56"×3.56") |
| Net Weight   | 0.64kg (1.41lb)                           |
| Gross Weight | 0.77kg (1.70lb)                           |

**Ordering Information**

| Type        | Part Number            | Description  |
|-------------|------------------------|--|
| 4MP Camera  | DH-HAC-HFW2401DP 3.6mm | 4MP HDCVI WDR IR Bullet Camera, PAL                    |
|             | DH-HAC-HFW2401DN 3.6mm | 4MP HDCVI WDR IR Bullet Camera, NTSC                   |
| Accessories | PFA135                 | Junction box (For use alone or with PFA150 pole mount) |
|             | PFA150                 | Pole mount (For use with PFA135 junction box)          |

**Accessories**

Optional:



PFA135  
Junction box



PFA150  
Pole mount

| Junction Mount | Pole Mount      |
|----------------|-----------------|
| PFA135         | PFA135 + PFA150 |
|                |                 |

**Dimensions (mm/inch)**

